International Travel Charger 140W GaN technology, Four port USB Type-A(1x) and -C(3x), PPS + Power Delivery(PD) 3.1 Support





Product Name:

International Travel Charger 140W GaN technology, Four port USB Type-A(1x) and -C(3x), PPS + Power Delivery(PD) 3.1 Support

Product Series: Power Charger

Product Code: CAC-1917

EAN code: 8719214472733

UPC code: 841615102976

Description:

The Club 3D CAC-1917 International Travel Charger 140W GaN technology, Four port USB Type-A(1x) and -C(3x), PPS + Power Delivery(PD) 3.1 Support is a high-performance and fashionable design travel charger.

Versatility: Perfect solution for business travelers and power users, with interchangeable plugs to fit different countries' needs and multiple ports. This means you only need one charger for all your devices, and you don't have to worry about carrying multiple adapters.

Portability: Highly portable and easy to carry (466 gr / 16.43 oz) in a backpack or luggage, making it ideal for business travelers who need to stay connected on the go without being weighed down by bulky chargers.

Powerful charging: The 142 Watt charger charges multiple devices simultaneously at high speed, while improving the life of your batteries at the same time. Ensuring busy travelers can stay productive on the move without waiting around for hours. Built-in safeguards protect your devices against excessive current, overcharging and overheating(OCP-OTP-SCP-OVP).

Features:

- Internal chip allows an input voltage of 100-240VAC 50/60Hz
- GaN technology
- 140Watt of output power in total(single port usage):
 - Output USB Type-**C1**: PD3.1:5~15V≤3A(45Watt), 20V~28V≤5A(140Watt MAX) PPS: 5V-21V/5A (100Watt MAX)
 - Output USB Type-**C2**: PD3.1: 5V3A/9V3A/15V3A/20V3.25A(65Watt MAX) PPS: $3.3V-21V \le 3.25A(65Watt MAX)$
 - Output USB Type-**C3**: PD3.1: 5V3A/9V3A/15V3A/20V3.25A(65Watt MAX) PPS: $3.3V-21V \le 3.25A(65Watt MAX)$

Output of the USB **Type-A** port can convey $5V \le 2.4A(12W)$

- The maximum power output for single USB Type-C port is 140Watt
- Power Delivery(PD) 3.1Support
- Accurate limited current output and over current protection(OCP)
- Overload protection and over voltage protection(OVP)
- Short circuit protection(SCP)
- Over temperature protection and remove the fault condition autorecovery(OTP)
- Compliant with CE, FCC standards.
- Mains connector interchangeable
- Portable and convenient to use.
- Specially designed for your USB Type-C supported devices.

OS Support:

■ All

In the box:

- CAC-1917 International Travel Charger 140W GaN technology, Four port USB Type-A(1x) and -C(3x), PPS + Power Delivery(PD) 3.1 Support
- 4 different mains connectors interchangeable
- 1x USB Type-C Power Certified 240W(48V/5A) EPR cable(1 m / 3.28 ft)

Please use one of our Extension/Adapter cables to connect to your devices: In case you need assistance to choose the correct cable, please visit our website www.club-3d.com or feel free to mail us at support@club-3d.com and it will be our pleasure to assist you.



Available Interfaces

nput:

■ 1x Mains connector interchangeable

Output:

- USB Type-A Female(1x)
- USB Type-C Female(3x)

Other info:

- Box size: 11 x 13 x 5.5cm / 4.33 x 5.12 x 2.16"
- Device size: 9.6 x 7.6 x 3.1 cm / 3.78 x 2.99 x 1.22"
- USB (Power) Cable length approx.: 1 m / 3.28 ft
- Device Weight(Depending on mains connector): approx. 387 gr / 13.65 oz
- USB Cable Weight: 34 gr / 1.2 oz
- Box Weight: 38 gr / 1.34 oz
- LDPE Bag Weight: 6 gr / 0.21 oz
- Total Weight(depending on mains connector) approx.: 466 gr / 16.43 oz
- Meets ROHS, FCC, and CE EMI requirements
- Warning Safe Usage Only to be used at altitude 2000 meters/6562 feet and

		CAC-1917 OUTPUT				CAC-1917 OUTPUT	
Use Case	Port	PD0	Use Case	Use Case	Port	PDO PDO	Use Case
Single Port Use	USB-C1	PD3.1:5V3A/9V3A/15V3A/20V5A/28V5A (140W MAX)	cı	Three Port Use	USB-C1	PD3.1:5V3A/9V3A/15V3A/20V3.25A	
		PPS:5V-21V/5A (100W MAX)				PPS:5V-21V3.25A (65W MAX)	
	USB-C2	PD3.1:5V3A/9V3A/15V3A/20V3.25A	(2		USB-C2	PD3.1:5V3A/9V3A/15V3A/20V2.25A	(1+C2+C3
		PPS:3.3V-21V3.25A (65W MAX)				PPS:3.3V-16V3A (45W MAX)	
	USB-C3	PD3.1:5V3A/9V3A/15V3A/20V3.25A	G		USB-C3	PD3.1:5V3A/9V2.22A	
		PPS:3.3V-21V3.25A (65W MAX)				PPS:3.3V-11V2.2A (20W MAX)	
	USB-A	5V2.4A (12W MAX)	A		USB-C1	PD3.1:5V3A/9V3A/15V3A/20V3.25A	
Dual Port Use	USB-C1	PD3.1:5V3A/9V3A/15V3A/20V3.25A	Port			PPS:5V-21V3.25A (65W MAX)	C1+C2/
					USB-C2	PD3.1:5V3A/9V3A/15V3A/20V3.25A	G+A
		PPS:5V-21V3.25A (65W MAX)			/USB-C3		
	USB-C2	PD3.1:5V3A/9V3A/15V3A/20V3.25A		11+A	USB-A	5V2.4A (12W MAX)	
	/USB-C3	PPS:3.3V-21V3.25A (65W MAX)			USB-C2	PD3.1:5V3A/9V3A/15V3A/20V2.25A	
	USB-C1	PD3.1:5V3A/9V3A/15V3A/20V5A	C1+A			PPS:3.3V-16V3A (45W MAX)	
		PPS:5V-21V/5A (100W MAX)			USB-C3	PD3.1:5V3A/9V2.22A	C2+C3+A
	USB-A	5V2.4A (12W MAX)			030-03	PPS:3.3V-11V2.2A (20W MAX)	
	USB-C2	PD3.1:5V3A/9V3A/15V3A/20V2.25A	C2+G3 All Port Use		USB-A	5V2.4A (12W MAX)	
		PPS:3.3V-16V3A (45W MAX)		Port	USB-C1	PD3.1:5V3A/9V3A/15V3A/20V3.25A	
	USB-C3	PD3.1:5V3A/9V2.22A				PPS:5V-21V3.25A (65W MAX)	_
		PPS:3.3V-11V2.2A (20W MAX)			USB-C2	PD3.1:5V3A/9V3A/15V3A/20V2.25A	(1+(2+
						PPS:3.3V-16V3A (45W MAX)	G+A
	USB-C2	PD3.1:5V3A/9V3A/15V3A/20V3.25A		USB-C3	PD3.1:5V3A/9V2.22A		
	/USB-C3				PPS:3.3V-11V2.2A (20W MAX)		
	USB-A	5V2.4A (12W MAX)			USB-A	5V2.4A (12W MAX)	

Input:

Output:

Wall Power







