

Multi Stream Transport(MST)Hub DisplayPort™ 1.4 Triple Monitor 4K60Hz with DSC 1.2



Product Name

Multi Stream Transport(MST) Hub DisplayPort™ 1.4 Triple Monitor 4K60Hz with DSC 1.2

Product Series

Video Splitters

Itemcode

CSV-7300

EAN code

8719214471415

UPC code

841615101597

Description:

The Club-3D Multi Stream Transport(MST)Hub DisplayPort™ 1.4 Triple Monitor 4K60Hz with DSC 1.2 is an integrated solution that allow you to enjoy displaying content onto three different monitors / displays simultaneously under MST mode. The three screens can accommodate displaying different contents in parallel or by simply extending the existing screen, giving a panoramic view of the content which maximizes the user's visual experience. With its multi-display capabilities, this hub can serve as a convenient and hassle-free portable, alternative solution to the conventional docking station. Support G-Sync, FreeSync and VRR. It's the perfect solution for host devices which feature DP1.2 /1.4 graphic cards, for gaming and commercial applications.

Features:

- Compliant with DisplayPort™1.4 specification 4K60Hz with DSC 1.2
- Compliant with HDCP 2.2 specification
- Supports Triple Monitor 4K60Hz with DSC 1.2
- Supports dual 4K60Hz@24 bpp without compression
- DSC 1.2 transport and up to 4-slice decompression
- Supports G-Sync, FreeSync and VRR
- High Dynamic Range (HDR) video
- SST or up to 3 stream MST

Supported resolutions:

Video Resolution	Max. Resolution of Extended Display	DP1.2 HBR2	
		1x 4K30, 2x FHD60, 3x FHD30	
		DP1.4 HBR3	
		1x 4K60, 2x QHD30, 3x FHD60	
		DP1.4 HBR3 DSC 1.2	
		1x 5K60*, 2x 4K60, 3x 4K60	

* SST, and for monitors with build-in MST Hub

Display Mode	DP1.4 Output Port 1	DP1.4 Output Port 2	DP1.4 Output Port 3
Single	7680x4320*30Hz, 24bpp	Not Connected	Not Connected
Single	Not Connected	7680x4320*30Hz, 24bpp	Not Connected
Single	Not Connected	Not Connected	7680x4320*30Hz, 24bpp
Dual	3840x2160*60Hz, 30bpp	3840x2160*60Hz, 30bpp	Not Connected
Dual	3840x2160*60Hz, 30bpp	Not Connected	3840x2160*60Hz, 30bpp
Dual	Not Connected	3840x2160*60Hz, 30bpp	3840x2160*60Hz, 30bpp
Triple	3840x2160*60Hz, 24bpp	3840x2160*60Hz, 24bpp	3840x2160*60Hz, 24bpp

*Requirement: - Host must support DP1.4 with DSC1.2 feature

OS Support:

Microsoft Windows® 10

In the box:

- CSV-7300, 3 port DisplayPort™ 1.4 MST Hub 4K60Hz with DSC 1.2
- 1x USB Type A cable for powering the Hub 1 m / 3.28 ft
- Quick Install Guide

Available Interfaces:

- 1x Displayport™ Male for connecting to Host
- 3x Displayport™ Female for connecting to monitors
- 1x DC Power jack(5V / 2A)

Other info:

- Box size: 14.5 x 14.5 x 4.5 cm
- Box size: 5.7 x 5.7 x 1.77 inch
- Device size: 79 x 79 x 1.7 cm
- Device size: 3.11 x 3.11 x 0.67 inch
- Cable to Host : 13 cm / 5.12 inch
- Device Weight: 68gr / 2.4oz
- USB Type A power cable length: 100 cm / 39.37 inch
- USB Type A power cable weight: 24gr / .85oz
- LDPE Bag Weight: 5gr / .17oz
- Box Weight: 24gr / .85oz
- Total Weight: 121gr / 4.27oz
- Meets ROHS, FCC, and CE EMI requirements



w e c o n n e c t

Disclaimer: While we endeavor to provide the most accurate, up-to-date information available, the content on this document may be out of date or include omissions, inaccuracies or other errors. Therefore Club 3D does not accept any rights claimed on the content of this document. Please refer to a full overview of our Legacy Terms and Conditions on www.club-3d.com. All other brand names are trademarks or registered trademarks and are the property of their respective owners. All content is subject to change without prior notice.